

General Purpose Vertical Turning Center VTX-450



APPLICATION:



**& Many
More**

Suitable for Unbalanced & Heavy Jobs

SPECIFICATIONS:

Max Swing Dia	Ø 650mm
Max Turning Dia / Over Way Cover	Ø 560mm / Ø 440mm
Max Turning Length	400mm
Chuck Size	12"
Spindle Nose	A2-8
Spindle Motor Output (Cont. / 30 Min.)	12kw / 15kw (Optional 15kw / 18kw)
Spindle Speed	2500 rpm
Spindle Full Power Range	400 - 2500 rpm
X/Z axis Travel	300mm / 530mm
X/Z axis Rapid	20m / min.
Turret Station	8 - Station / 12 - Station
Tool Shank Size	25 x 25
Boring Bar Dia.	40mm
CNC Controller	Siemens 828D/FANUC Series Oi Mate-TD
Machine Weight	4300kg

OPTIONS:

Chip Conveyor
Live Tool Turret for Turn-Mill Applications
Special Work Holding
Loading - Unloading Automation



ANIL MECHATRONIX PVT. LTD.
Shed No. C1-B-24/1, Road No. G,
G.I.D.C. Aji Industrial Estate,
Rajkot : 360 003.

Phone : +91-281-2387007
E-mail : anmecx@gmail.com
web : www.anmecx.com